

INTERNAL CALIBRATION


FEATURES :-

- Automatic internal calibration with built in weight
- A built in under hook for below weighing system (optional)
- Easy to read LCD Display with back light
- Density measurement for solid and liquid (Optional)
- Standard RS 232 C interface
- Based on E.M.F.C. Technology
- S.S. Weighing Pan, Level Indicator, Adjustable Fit Full tare range up to max. Capacity of the Balance

ADDITIONAL FEATURES :-

In new this series balance the information system is based on 5 databases, which allows for several users to work with several products databases, and the registered weighing results can be subject to further analysis.

- Users (up to 10 users)
- Products (up to 1000 Products)
- Weighments (up to 1000 weighments)
- Tares (up to traes)
- ALIBI memory (up to 100 000 weighments)



TECHNICAL DATA

MODEL NO.	DWAI-124C	DWAI-224C	DWAI-314C
Max Capacity	120g	220g	310g
Readability (acc.)	0.1mg	0.1mg	0.1mg
Tare Range	Full		
Repeatability	±0.1mg		
Linearity	±0.2mg		
Pan Size	100mm		
Stabilization time	3-4 sec		
Communication	Interface 2 x RS232, Type A, Type B, USB optional Wifi		
Calibration	Internal Calibration		
Weighing Units	Muilt weighing Units		
Power	230 V / 11V AC or 120 V / 11 V AC		
Display	LCD DISPLAY WITH Back Light		
Working temperature	10°C - 40°C		
Net weight & gross weight	5.6/8.3 kg		